

SonicWALL TZ 190

NETWORK SECURITY

Secure 3G Wireless Broadband Networking in an Instant

- Instant 3G wireless broadband access
- High performance deep packet inspection firewall
- Integrated gateway anti-virus, anti-spyware and intrusion prevention**
- Support for both GSM and CDMA based 2G/3G networks
- Automated WAN failover and failback
- Intuitive configuration wizards
- Port level security
- Secure wireless LAN controller
- Global management and reporting

Organizations depend on high-speed broadband Internet connections for maximum employee productivity, and for exchanging confidential customer information and sensitive business data. In many instances this requires an Internet connection in areas where wired networks—DSL, leased line, ISDN and others—are unavailable or require time consuming installation and provisioning.

The SonicWALL® TZ 190, featuring a deep packet inspection architecture, enables organizations to establish secure 3G wireless broadband network access in an instant without the need for a wired Internet connection. By leveraging recent advances in 3G wireless broadband technologies, organizations can rapidly establish high-speed access for seasonal kiosks, mobile point-of-sale stations, portable ATM machines, disaster recovery networks and more.

The TZ 190 is a high-performance, multi-layered network security platform that integrates Type II PC Card* based 3G wireless broadband support, hardware accelerated IPSec VPN, automated failover/failback technologies and a deep packet inspection firewall. Built on SonicWALL's powerful SonicOS Enhanced operating system, the TZ 190 delivers advanced business continuity and networking features including ISP failover, policy-based NAT, bandwidth management and DDNS. The TZ 190 offers a deeper level of network security through the integration of real-time gateway anti-virus, anti-spyware, intrusion prevention and anti-spam capabilities for complete protection against malicious threats that originate either internally or from the Internet.

Features and Benefits

Instant 3G wireless broadband access enables secure networking even in areas where fixed broadband is impractical.*

A configurable, **high performance deep packet inspection firewall** provides enterprise-class protection for key Internet services such as Web, e-mail, file transfer, Windows services and DNS.

Support for **integrated gateway anti-virus**, **anti-spyware and intrusion prevention** delivers real-time protection against the latest viruses, spyware, software vulnerabilities and other malicious code.**

Worldwide 3G wireless broadband coverage is ensured through **support for both GSM and CDMA based 2G/3G networks** including 1xRTT, EV-DO, EV-DO rev A, UMTS, GPRS, EDGE and HSDPA. Integrated and **automated WAN failover and failback** ensures continuous uptime by failing over to an alternate WAN connection should the primary fail.

Intuitive configuration wizards simplify even the most complicated tasks, including VPN set-up and NAT configuration.

SonicWALL PortShield Architecture provides the flexibility to configure **port level security** for the LAN, providing protection between devices inside the LAN.

The TZ 190 functions as a **secure wireless LAN controller** that automatically detects and configures SonicWALL SonicPoint[™] 802.11a/b/g wireless LAN access points.

Award-winning Global Management System (GMS) provides comprehensive **global management and reporting** tools for simplified configuration, enforcement and management from a central location.

*PC Card sold separately. See http://www.sonicwall.com/us/tz190cards.html for supported cards. **Requires Gateway Anti-Virus, Anti-Spyware and Intrusion Prevention Service subscription



Specifications

SonicWALL TZ 190

Firewall Nodes S

Thewall	
Nodes Supported	Unrestricted
Stateful Packet Throughput	90+ Mbps
Gateway Anti-Virus Throughput	10 Mbps
Intrusion Prevention Throughput	8 Mbps
Gateway Anti-Spyware Throughput	6 Mbps
Connections	6,000
Policies	250 per zone
Denial of Service and Protection	22 classes of DoS, DDoS scanning attacks

VPN 3DES Throughp

Gateway

Appliance

01-SSC-6850

(1 year) 01-SCC-5844

01-SSC-5751

01-SSC-5505

(1 year) 01-SSC-5650

01-SSC-3515

SonicWALL TZ 190

Security Services

Comprehensive Gateway Security Suite

Gateway Anti-Virus, Anti-Spyware and

Content Filtering Service Premium Edition

Intrusion Prevention Service (1 year)

Content Filtering Service (1 year)

Dynamic Support 8x5 (1 year) 01-SSC-3502

Dynamic Support 24x7 (1 year)

3DES Throughput	30+ Mbps
AES Throughput	30+ Mbps
Site-to-Site VPN	15 tunnels max
Remote Access VPN	Upgradeable to 25 simultaneous users, includes 2 licenses
Encryption	DES, 3DES, AES (128, 192, 256)
Authentication	MD5, SHA-1
Key Exchange	IKE, Manual Key, Certificates (X.509)
XAUTH/RADIUS	Yes
L2TP/IPSec	Yes
Dead Peer Detection	Yes
DHCP over VPN	Yes
IPSec NAT Traversal	Yes
Redundant VPN	Yes

Deep Inspection Security Services

Gateway Anti-Virus, Anti-Spyware and Intrusion Prevention	Extensive signature database. Peer-to-peer and instant messaging control and signature updates through Distributed Enforcement Architecture between all interfaces
Content Filtering Service (CFS)	URL, keyword and content scanning, ActiveX®, Java Applet, and Cookie blocking
Gateway-enforced Network Anti-Virus	HTTP/S, SMTP, POP3, IMAP and FTP, Enforced McAfee™ Client, E-mail attachment blocking
Bundled Features	90 days 8x5 or Software and Firmware Updates. Global VPN Clients and services as described above
Wireless LAN	

Wireless I AN

Wireless LAN Controller	Included
SonicPoint Versions	802.11a/b/g and 802.11b/g
Managed SonicPoints	Maximum 8 per interface, 16 per appliance
WLAN Standards	IEEE 802.11a, 802.11b, 802.11g, 802.11d, 802.11i (Requires SonicOS Enhanced 3.7 or greater)
Power over Ethernet	SonicPoints support 802.3af PoE
WLAN Security	WPA, 64/128/152-bit WEP, TKIP, AES, 802.11i (Requires SonicOS Enhanced 3.7 or greater)

3G Wireless WAN

Wireless Signal
Strength Indicator
PC Cards Supported*

Variable rate LED and Graphical User Interface

Novatel Wireless Merlin PC720 Novatel Wireless Merlin S620 (Sprint Mobile Broadband Card) Novatel Wireless Merlin S720 (Sprint Mobile Broadband Card) Novatel Wireless Merlin V620 Option GlobeTrotter GT MAX Option GlobeTrotter GT MAX 7.2 ready Option GlobeTrotter HSDPA Ontion GT Max 3.6 Sierra Wireless AirCard 860

Typical WWAN Throughput** 1.000 to 2.000 kbps EV-DO Rev A EV-DO 400 to 700 kbps 80 to 100 kbps 1xRTT 1,000 to 2,000 kbps 300 to 500 kbps HSDPA UMTS EDGE 200 to 400 kbps GPRS 80 to 100 kbps Bandwidth Usage Day, week, month and year upload and download Reporting traffic statistics Card Insert/Removal Alerts sent through wired WAN interface to remote Alerting administrator or Global Management System WWAN Bandwidth FIFO, CBQ, RFC 2309, per-interface and per Management access-rule, and guaranteed bandwidth, maximum bandwidth, priority LAN LAN Interfaces (8) 10/100 Ethernet PortShield Maximum eight custom security zones Port Speed 10 Mbps, 100 Mbps, Auto, Off Full, Half, Auto Duplex Traffic Stats TX/RX byte count, TX/RX Networking DHCF Internal server, relay NAT Modes 1:1, many:1, 1:many, many:many, flexible NAT, PAT Policy-based Routing Routing decisions based on combination of source IP, destination IP, service WAN Modes NAT and Transparent modes with static or dynamic addressing DDNS Support dyndns.org, vi.org, no-ip.com and change-ip.com RADIUS, LDAP, AD, Internal database (max 150 users) Authentication Hardware (8) 10/100 LAN, (1) 10/100 WAN, (1) 10/100 OPT Interfaces Memory (RAM) 128 MB Flash 16 MB Input Power 100 to 240 VAC, 50-60 Hz, 1 A Maximum Power 12.7 Watts Consumption Total Heat Dissipation 43.3 BTU MTBF 9.6 Years ICSA Firewall 4.1, ICSA IPSec VPN 1.0d, FIPS 140-2, VPNC AES, Common Criteria EAL-2 Certifications (pending) 10.0 x 7.0 x 1.2 inches Dimensions 25.4 x 17.8 x 3.0 cm Weight 2.0 lbs 0.92 kg Shipping Weight 4.75 lbs 2.1 kg

2.75 lbs 1.3 kg Major Regulatory FCC Class B, ICES Class B, CE, C-Tick, VCCI Class B, NOM, UL, cUL, TUV/GS, CB, RoHS, WEEE 40-105° F, 5-40° C 10-90% non-condensing

* For a complete list of supported cards check

WEEE Weight

Compliance

Environment

Humidity

http://www.sonicwall.com/us/tz190cards.html

** Actual throughput depends on several factors including proximity to the cellular tower, weather conditions and network congestion. Also, the chart shows download throughputs. Upload throughputs will be lower.

SonicWALL Value-added Security Services

SonicWALL network security appliances integrate seamlessly with an expanding array of value-added security services to provide a comprehensive security solution. Gateway anti-virus, anti-spyware, intrusion prevention, desktop enforced anti-virus and content filtering can be deployed over both the wired and wireless LANs.

SonicWALL, Inc.

1143 Borregas Avenue Sunnyvale CA 94089-1306 T +1 408.745.9600 www.sonicwall.com F +1 408.745.9300

SONICWALL

©2007 SonicWALL, Inc. is a registered trademark of SonicWALL, Inc. Other product names mentioned herein may be trademarks and/or registered trademarks of their respective companies. Specifications and descriptions subject to change without notice. 02/07